

# ARBO®

## ARBOShield Pro Class A High-Tack Sealing Tape

ARBOSHIELD

ARBO Façade Solutions (ARBO FS) is the new name for a ground-breaking initiative from ARBO, one of the longest established names in UK construction materials.

ARBOShield Pro Class A High Tack Sealing Tape has been specifically designed to provide a strong and resilient seal when secured against a membrane lap or detailing such as window and/or door openings.

### MAIN APPLICATIONS

ARBOShield façade solutions can be used in both new build and refurbishment installations, in commercial, industrial, residential and retail environments. Curtain walling, large scale façades or even modular and off-site construction methods can all be effectively weatherproofed and fire protected.

ARBOShield Pro Class A High Tack Sealing Tape can also be used to repair minor rips and tears in ARBOShield Pro breather membrane and ARBOShield Pro Class A Air & Vapour Control Layer. Please contact ARBO technical services for advice or guidance on suitability to repair or replace any installation damage. For further details, contact ARBO Technical Services [techservices@arbo.co.uk](mailto:techservices@arbo.co.uk)



### SIZE

Roll Size

100mm x 50m

[www.arbo.co.uk/ARBOShield](http://www.arbo.co.uk/ARBOShield)

**CARLISLE**  
CM EUROPE

## TECHNICAL DATA

Product	Standard	Description	Performance
ARBOShield Pro Class A High-Tack Sealing Tape	EN 13501-1:2018	Reaction to Fire	A2-s1,d0
		Peel Adhesion Test	10N
		Service Temperature	0°C - 60°C
		Short Term Temperature	-20°C- 100°C

### FIXING INSTRUCTIONS

ARBOShield Pro High Tack Sealing Tape has been designed to provide the strongest of seals when secured against a membrane lap or detailing such as window and/or door openings. ARBOShield Pro High Tack Sealing Tape can also be used to repair minor rips and tears in the membranes or AVCL on application.

Please contact ARBO Technical Services [techservices@arbo.co.uk](mailto:techservices@arbo.co.uk) for full guidance on suitability to repair or replace any installation damage.

### STORAGE

ARBOShield Pro Class A High Tack Sealing Tape should be stored in cool, dry conditions in the upright position.

### HEALTH & SAFETY

The material Safety Data Sheet must be read and understood before use. All relevant standards should be observed on site, including manual handling and working at height.

**IMPORTANT:** The information in this leaflet is given in good faith and based on results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms and conditions of sales, a copy of which is available on request.

### ASSOCIATED PRODUCTS

ARBOShield Pro Class A W1 Breather Membrane  
ARBOShield Pro Class A Air & Vapour Control Layer  
ARBOShield Pro Class B W1 Breather Membrane  
ARBOShield Pro External Perimeter Class A Membrane (EPAM)  
ARBOShield Pro Class A High-Tack Sealing Tape  
ARBOProtect Pro  
ARBO Intumescent and Fire-Resistant Mastics, Sealants and Foams  
ARBOSeal Pro Sealing Tapes

CARLISLE® Adshead Ratcliffe & Co. Ltd United Kingdom

Derby Road | Belper  
Derbyshire

DE56 1WJ  
United Kingdom

T +44 (0)1773 826661  
F +44 (0)1773 821215

E [info.arbo@ccm-europe.com](mailto:info.arbo@ccm-europe.com)  
[www.arbo.co.uk](http://www.arbo.co.uk)

**UK  
CA**